

RRE160/ E
BT Reflex R/E-seriesSelling Price
Ex Works Std or Option

Model	RRE160 standard	EURO	Std or Option
Drive unit	Standard	€0	standard
Maximum speed	Standard	€0	standard
	347 mm (600 Ah) Max lift height 9500 mm	€54	standard
Battery fitting	On support arms 18)	€0	standard
Battery plug	Prepared for fixed battery, inclusive fixed cable for one battery	€0	standard
Mast	Triplex hilo 6300 mm	€527	standard
Distance between	900 mm. (b1=1270 mm)	€0	standard
Support wheel	Standard without brake ø300	€0	standard
Hydraulic control	Separate levers	€0	standard
Direction switch	Hand operated	€0	standard
	Medium backrest, textile	€0	standard
	Integr. Sideshift, Tilt 4° up, 2° down, 4-functions.	€539	standard
Fork length	40x100; L=1000 or 1150mm	€0	standard
Handling facilities	Load Info Display, LID 8) (also included in SAFETY+)	€581	standard
	Height indication	€355	standard
Total Ex Works price:		€16.655	
Transport*:		€746	
Total DAP price:		€17.401	

* Transport costs for Havi Europe ex RUS, TR, UKR. Transport prices for RUS, TR, UKR on demand.

Drive Unit	Standard, cold store	€937	option
	Standard, cold store with heated cabin	€8.182	option
	Tilting cab 1) 24) (also included in DRIVEABILITY+)	€1.399	option
	Tilting cab, cold store with heated cabin 1) 24) (also included in DRIVEABILITY+)	€9.582	option
	Drive in rack. Width 910 mm from height 1520mm	€818	option
Mast	Triplex hilo 7000 mm	€646	option
	Triplex hilo 8000 mm	€764	option
	Triplex hilo 8500 mm	€818	option
	Triplex hilo 9000 mm	€937	option
	Triplex hilo 9500 mm	€1.055	option
Support wheel	Standard with brake (also included in PRODUCTIVITY+)	€883	option
	Medium backrest, textile, heated	€162	option
Fork Length	Load support standard (height above fork; 1000 mm) 32)	€140	option
Overhead Guard Options	Metal-guard on overhead guard	€215	option
	Warning light on overhead guard	€248	option
	Height preselector (must be combined with LID) 9)	€237	option
	One colour monitor and one camera on fork (incl. wiring) 10) 19)	€1.927	option
	Writing table, A4 35) 43)	€43	option
	Roller bed, specify battery 42)	€355	option
	Battery change table	€1.755	option
	Battery plug and 3m extension cable, adapter for battery change	€76	option
	T.W.I.S., access to information through internet. Incl DHU + antenna	€248	option
	Shock sensor	€108	option
BATTERY	Battery 48V, 620Ah incl BFS	€3.121	
CHARGER	High frequency charger HF 48/100	€841	

NOTES

- 1) Height indicator required
3) 1 hose reel must be added
4) 2 hose reels must be added
5) Not with camera on forks
6) Max 2 hose reels. Do not combine 1/4 and 3/8". First choice:
Left, Second choice: Right. Middle is recommended for drive in rack
7) Only heated cabin
8) Weight and height indicator included.
9) 1 tilt angle 4° up, 2° down or automatic U-tilt recom.
10) Ref no required when combined with fork spreader
11) Not cold store without heated cabin.
12) Ref no required
13) Not with drive in rack
14) Not cold store
15) LID required
16) Key/ Card programmer is to be ordered from B1 Europe AB / Parts division
17) Not with 1050mm between support arms
18) Not on 1050, 1100 & 1300mm between support arms
19) If Drive-in without heated cab; Vertical L-bar is required
20) Max length 1.5 x normal fork
21) Not together with load support
22) Only in combination with "Support wheel with brake"
23) Add one hose reel left 1/4"
24) Only combined with seat "high backrest"

- 25) Reduced over lap
26) Mast height h1 increases 100mm
27) Not available on mast heights below 6300 mm
28) Not available on mast heights below 1000 mm if battery comp is 2/5 (34/mm)
30) Only for lift heights between 6300 and 9500 mm
31) Not with battery compartment 2/5 mm
32) Not with telescopic forks
33) Not with Heated cabin
34) Not with Height preselector
35) Not with P/L I/C holder
36) Can not be combined with "Kear view mirror" + "One colour monitor" if open cab
38) Only 1 of the 2 UCUUC converters with outlet in dash is incl. in HKUUC11V11Y+ package
39) Arm rest and Hip guard can not be combined
40) Exceptions: Ref No. not included in Special products price list, Cold store, Scale
41) Not with fire extinguisher
42) Must be combined with battery plug "Prepared for battery change"
43) Must be combined with Option "Horizontal L-bar"
44) Only one "outlet in dash board" is possible to add to the machine
45) Not with integrated fork spreader
46) Not with Protection for sideshift cylinder
47) Not with U-sideshift
48) Not available lift heights above 9500 mm
49) Basic seat must be added. Not with Cold store, PRODUCTIVITY+, DRIVEABILITY+, 1 lift. Cab or High drive, speed
50) Not with Hip guard, Armrest or Heel seat belt

